35 CAB 45 CAB 55 CAE

- MITSUBISHI EURO III engines with liquid cooling
- Hydrostatic steering with independent hydraulic system
- Hydraulic system with 30 l/min. pump and 6 way auxiliary hydraulic control valves
- Electro-hydraulically operated front and rear differential locking

New Cab

Antonta



| FECHNICAL DATA | R1.35 CAB | | | | R1.45 CAB | | | | R1.55 CAB | | | | | |
|--|--|--------------------------------|----------------------|---------------------|-------------|---------------------|---------------|------|-------------|---------------------|-------|-----|--|--|
| | Version | 2WD | | 4WD | | 2WD | | 1WD | á | 2WD | 4 | ND | | |
| NGINE | | MITS | MITSUBISHI EURO III | | | MITSUBISHI EURO III | | | | MITSUBISHI EURO III | | | | |
| Cylinders/Displacement | no./cm ³ | | 4/1500 | | | 4/1500 | | | | 4/1758 | | | | |
| spiration | | | Natural | | | Turbo | | | | Turbo | | | | |
| Nax. homologated power (2000 |)/25/CE) HP/kW | | 39/28,5 | | | 43/31,5 | | | 51/37 | | | | | |
| Aax. homologated power (ECE F | | 35/26 | | | 41/30 | | | | 47/34,5 | | | | | |
| lominal engine speed | rpm | | 3000 | | | 3000 | | | | 3000 | | | | |
| lax. torque | Nm | | 83 | | | 100 | | | 122 | | | | | |
| lax. torque engine speed | rpm | | 1900 | | | 2100 | | | 2000 | | | | | |
| ooling | liquid | | | | | | | | | | | | | |
| ngine control | mechanical | | | | | | | | | | | | | |
| ir cleaner | dry with safety cartridge | | | | | | | | | | | | | |
| ilencer underhood | | | with lateral exhaust | | | | | | | | | | | |
| uel tank capacity | uel tank capacity | | | | | 38 (m | ain fuel tanl | d | | | | | | |
| четтанк сарасну | | 15 (auxiliary fuel tank) | | | | | | | | | | | | |
| ngine hood | single piece, hinged opening | | | | | | | | | | | | | |
| IMENSIONS AND WEIGHTS (with | | 320/70 R 20 | | | 360/70 R 24 | | | | 360/70 R 24 | | | | | |
| 1ax. length without link arms | mm | | 2950 | | | 2980 | | | | 2980 | | | | |
| /idth min max. | mm | 1 | 1220*-1360 | | | 1360-1675 | | | | 1360-1675 | | | | |
| 1ax. height at cab | mm | | 2135 | | | 2195 | | | | 2195 | | | | |
| round clearance | mm | | 345 | | | 390 | | | | 390 | | | | |
| Vheelbase | mm | 1745 | | | | 1745 | | | | 1745 | | | | |
| ront track min max. | mm | | 970-1120 | | | 1040-1315 | | | | 1040-1315 | | | | |
| lear track min max. | mm | 820-1020 | | | | 1005-1320 | | | | 1005-1320 | | | | |
| nimum steering radius without braking mm | | | 2600 | | | 2600 | | | 2600 | | | | | |
| Veight with cab | ght with cab kg | | 1350 | | | 1420 | | | 1420 | | | | | |
| RANSMISSION | | | | | | | | | | | | | | |
| earbox clutch | mechanically operated | | | | | | | | | | | | | |
| Aechanical gearbox 12 FWD + | 4 synchronised gears, 3 gear ranges (min. speed: 0.89 km/h) | | | | | | | | | | | | | |
| lechanical gearbox 16 FWD + | 4 synchronised gears, 4 gear ranges with creeper (min. speed: 0,24 km/h) | | | | | | | | | | | | | |
| 1ax. speed | 30 | | | | | | | | | | | | | |
| huttle | | mechanical, synchronised | | | | | | | | | | | | |
| lear differential lock | | electro-hydraulically operated | | | | | | | | | | | | |
| 6 FWD + 16 REV GEARBOX - SP | EED IN KM/H <u>at en</u> | GINE SPEED OF 3 | 3000 RP <u>M</u> | WITH 360 <u>/70</u> | R 24 REA | R TYRES | | | | | | | | |
| 1 SR 2 SR 3 SR | 4 SR 1 | 2L | ЗL | 1M | 4 L | 2M | ЗM | 4M | 1H | 2H | ЗH | 4 | | |
| 0.24 0.37 0.56 | 0.84 0.9 | 1.34 | 2.08 | 2.29 | 3.14 | 3.47 | 5.26 | 7.92 | 9.26 | 14.06 | 21.27 | 32. | | |

| BRAKES AND STEERING | | | | | | | |
|---|---|--|--|--|--|--|--|
| Braking system | mechanically operated | | | | | | |
| | rear discs in oil bath | | | | | | |
| Hydrostatic steering | with independent pump | | | | | | |
| Steering angle | 57° | | | | | | |
| FRONT AXLE | | | | | | | |
| Туре | portal | | | | | | |
| Front mudguards | swivelling | | | | | | |
| Drive engagement | mechanically operated | | | | | | |
| Front differential lock | electro-hydraulically operated | | | | | | |
| Front ballast | (4) 25 kg weights, 15 kg weights | | | | | | |
| VENTRAL P.T.O. | | | | | | | |
| Clutch | mechanically operated | | | | | | |
| Speed rpm | 2000 | | | | | | |
| FRONT P.T.O. | | | | | | | |
| Clutch | multiple discs in oil bath | | | | | | |
| Speed rpm | 1000 | | | | | | |
| Operation | electro-hydraulically operated, push-button control | | | | | | |
| REAR P.T.O. | | | | | | | |
| Clutch | mechanically operated | | | | | | |
| rpm | 540-1000 | | | | | | |
| Speed rpm | 540-540 ECON | | | | | | |
| | synchronised P.T.O. | | | | | | |
| HYDRAULIC LIFT | | | | | | | |
| Rear power lift | mechanical | | | | | | |
| Implement control | depth and draft control | | | | | | |
| Maximum lifting capacity kg | 1200 | | | | | | |
| Pump delivery I/min. | 30 | | | | | | |
| Auxiliary hydraulic control valves no. ways | 4/6 | | | | | | |
| Front lift | original integrated | | | | | | |
| Front lift | maximum lifting capacity 400 kg | | | | | | |
| DRIVING POSITION | | | | | | | |
| | original sound-proofed with platform | | | | | | |
| Cab | on silent-block mountings, rear | | | | | | |
| | windscreen wiper, 4 work lights | | | | | | |
| Cab conditioning | air conditioning, ventilation and heating | | | | | | |
| Gear levers | under steering wheel | | | | | | |
| Lift control levers | on console to the right of the driving position | | | | | | |
| Driver's seat | complete with safety belt | | | | | | |
| | | | | | | | |

DEALER CONTACT

aim at LAMBORGHINI is to del

As

data and illustn

Lamborghini

SAME DEUTZ-FAHR GROUP S.p.A.

Viale Cassani, 14 _ 24047 _ Treviglio (BG) _ Italy _ Ph: +39 0363 4211 _ www.samedeutz-fahr.com

SAME DEUTZ-FAHR U.K. LTD. Barby Lane, Barby, Nr Rugby _ CV23 8TD _ WARWICKSHIRE _ UK _ www.lamborghini-tractors.com

Akros

Company with

Quality System Certified in compliance with ISO 9001:2000 SPECIALISED LUBRICATION FOR LAMBORGHINI

* Available in a narrow axle version with 280/70 R 18 rear tyres. Minimum width: 1165 MM PLEASE NOTE: REVERSE SPEEDS ARE SLIGHTLY HIGHER THAN THE CORRESPONDING FORWARD SPEEDS

The above specifications refer to tractors with all available equipment. For standard equipment and options, refer to the current price list and ask your local dealer for details.