

STRIKE CM

105 | 115

Stage V



TECHNICAL DATA		STRIKE CM	
		105 115	
ENGINE			
Model		FARMotion 45	
Emission level		Stage V	
Cylinders/Displacement	nº/cc	4/3849	
Bore/Stroke	mm	103/115.5 ■	
Turbo Intercooler Common Rail injection	bar	2000	
Max. power (ECE R120)	kW/HP	78/106 85/116	
Power at rated engine speed (ECE R120)	kW/HP	74/101 80.6/110	
Max. torque	Nm	433 472	
Engine speed at maximum torque	rpm	1400	
Electronic engine control	·		
PowerCore air filter			
Fuel tank capacity	1	95	
AdBlue tank capacity	1	11	
EAT	System	DOC+DPF+SCR	
TRANSMISSION	T	074350	
SDF transmission		CT4150	
Gearbox Shuttle	Type	4 gears x 2 ranges x OverDrive or 4 gears x 3 ranges Mechanical	
N°of speeds (OverDrive)	nº	16+16	
N° of speeds (creeper)	nº	12+12	
PTO		TL TL	
Electrohydraulic engagement			
540/540ECO			
540/1000			
LIFT			
Mechanical rear lift			
Rear lift capacity	kg	3170	
HYDRAULICS			
Pump flow	I/min	50+25	
Rear spool valves (STD)	nº	3	
Rear spool valves (OPT) Mid mounted hydraulic ways	nº of would	3+2 diverters (10 rear ways) 2	
BRAKES AND STEERING	nº of ways	2	
Multi-plate wet lateral steering clutches		•	
Wet band steering brakes			
Pedal operated service brake			
TRACKS			
Number of rollers	nº	6	
Manual chain tightener			
Track type		Steel	
Number of shoes	nº	40	
Shoe width	mm	400 or 450	
Dry chains			
Lubricated chains DRIVING STATION		u u	
Platform suspended on Silent-Block		•	
2-post foldable safety frame		- I	
4-post safety frame			
Sun roof canopy			
Driving seat with mechanical suspension			
2+2 Halogen working lights on roof			
2+2 LED working lights on roof			
Aftermarket cab prearrangement			
DIMENSIONS AND WEIGHTS - STRIKE CM WIDE WITH ST	1		
Shoe width	mm	450	
Wheelbase	mm	1850	
Max. length Total height	mm	3550 2320	
Width	mm	1800	
Unladen weight	kg	5225	
DIMENSIONS AND WEIGHTS - STRIKE CM NARROW WITH			
Shoe width	mm	400	
Wheelbase	1	400 1850	
	mm		
Wheelbase	mm mm	1850 3550 2600	
Wheelbase Max. length	mm mm mm	1850 3550	

STD ■ OPT □ Not available -

www.lamborghini-tractors.com



