



- FARMotion Stage III B 3 cylinder engines with turbo intercooler and Common Rail injection.
- Mechanical transmission 15+15 or 30+15 with underdrive and super-creeper gear (maximum speed 40 km/h at eco engine speed).
- 50 l/min. hydraulic system and hydraulic distributors with up to 6 couplers.
- Mechanically controlled lift with 2,500 kg capacity (or 3,500 kg in optional configuration).
- 3-speed power take-off and ground speed PTO.
- All wheel braking system with wet disc brakes on all four wheels.
- New cabin with highly ergonomic control layout.

# SPIRE Trend

70 | 80 | 90 | 100




TECHNICAL DATA		SPIRE Trend			
		70	80	90	100
ENGINE					
Emissions compliance		Stage III B	Stage III B	Stage III B	Stage III B
Manufacturer		SDF	SDF	SDF	SDF
Series		FARMotion	FARMotion	FARMotion	FARMotion
Cylinders/capacity	n°/cm³	3/2887	3/2887	3/2887	3/2887
Turbo intercooler		●	●	●	●
Maximum power (ECE R120) at 2000 rpm	kW/HP	48/65	55,4/75	65/88	71/97
Rated power (ECE R120) at 2200 pm	kW/HP	48/65	55,4/75	61,6/84	67,3/92
Max. torque @ 1600 rpm	Nm	292	342	354	369
Torque rise	%	41	43	32	27
Electronic engine governor system		●	●	●	●
Fuel tank capacity	Litres	90	90	90	90
SHUTTLE					
Synchronised mechanical reverse shuttle		●	●	●	●
MANUAL GEARBOX					
5-speed gearbox 15+15 ECO with super-creeper gear (40km/h ECO)		●	●	●	●
5-speed gearbox 30+15 ECO with with underdrive and super-creeper gear (40km/h ECO)		○	○	○	○
REAR PTO					
Mechanically controlled		●	●	●	●
PTO 540/540ECO		●	●	●	●
540/540ECO/1000 PTO		○	○	○	○
Ground-speed PTO		○	○	○	○
FRONT AND REAR AXLE					
Electrohydraulically engaged 4WD		●	●	●	●
Electrohydraulically commanded differential lock		●	●	●	●
BRAKES AND STEERING					
Independent parking brake		●	●	●	●
Hydraulic trailer braking		○	○	○	○
Hydrostatic steering with independent pump		●	●	●	●
Steering angle		55°	55°	55°	55°
LIFT					
Mechanically controlled rear lift		●	●	●	●
Rear hitch lift capacity	kg	2500	2500	2500	2500
Rear lift capacity with supplementary rams	kg	3,500	3,500	3,500	3,500
HYDRAULIC SYSTEM					
Pump output (std)	l/min	50	50	50	50
Rear auxiliary hydraulic distributors	No. of ways	4/6	4/6	4/6	4/6
CAB					
Digital display		●	●	●	●
Height and tilt adjustable steering column		●	●	●	●
Air conditioned		○	○	○	○
High-visibility cab roof		○	○	○	○
DIMENSIONS AND WEIGHTS					
Standard front tyres		280/85 R20"	280/85 R20"	360/70 R20"	360/70 R20"
Standard rear tyres		380/85 R28"	380/85 R28"	420/70 R30"	420/70 R30"
Max. length	mm	3860	3860	3860	3860
Width	mm	1795	1795	1882	1882
Max. height at cab	mm	2470	2470	2495	2495
Wheelbase	mm	2100	2100	2100	2100
Weight	kg	3200	3200	3200	3200

STD ● OPT ○ Not available -

DEALER

[www.lamborghini-tractors.com](http://www.lamborghini-tractors.com)

Lamborghini Trattori is a brand of  SDF

